# VALIDATION OF THE BCH-ONTOLOGY

O. Zalamea<sup>1, \*</sup>, G. García<sup>1</sup>

<sup>1</sup> CPM project – University of Cuenca, Av. 12 de Abril y Loja, Cuenca, Ecuador - (olga.zalameap, gabriela.garcia)@ucuenca.edu.ec

#### **Commission II - WG II/8**

KEY WORDS: BCH-ontology, Semantic web, Ontology evaluation, CIDOC-CRM, CityGML, MONDIS

#### **ABSTRACT:**

In the heritage domain, capturing facts and knowledge for preventive conservation of Built Cultural Heritage (BCH) requires access to a large variety of data. It is a multidisciplinary activity and uses heterogeneous terminologies. In this regard, the BCH-ontology has been developed to facilitate integration and exchange of heterogeneous built cultural heritage information. The BCH-ontology reuses three already developed ontologies: Geneva City Geographic Markup Language (Geneva CityGML), Monument Damage ontology (Mondis), and CIDOC Conceptual Reference Model (CIDOC-CRM). Additionally, it provides a complete semantic framework by defining some classes and properties for improving BCH management. This paper presents the validation of the BCH-ontology ontological model to determine whether the ontology is able to represent BCH data under a preventive conservation approach. The San Luis seminary is a historical building built in the late XIX century in Cuenca-Ecuador and it is employed as use case. This validation allowed the identification of further use cases where the ontology offers a potential additional value in the BCH-domain.

# 1. INTRODUCTION

#### 1.1 Built cultural heritage domain

Built Cultural Heritage (BCH) is characterized by a plethora of heterogeneous information that is gathered by several stakeholders. International charters such us the Athens (ICOMOS, 1931), Venice (ICOMOS, 1964), and Burra (ICOMOS, 2003) charters recommend applying a preventive conservation approach for BCH-management.

Preventive conservation of BCH suggests conservation actions considering not only the assessment of state but also periodic assessments of risks and threats. Thus, there is a necessity to integrate and share this information (Hart, 2008). The following section explores some initiatives designed to facilitate this necessity.

#### **1.2** Preventive conservation approach

The preventive conservation approach for managing BCH demands a cyclical and systemic process of conservation actions. It goes beyond the assessment of state of conservation to include periodic assessments of risks and threats. It is meant to facilitate early damage detection by addressing first the deterioration causes so that intervention can be kept to a minimum (Forster, Kayan, 2009).

According to the ICOMOS Charter -Principles for the Analysis, Conservation and Structural Restoration of Architectural Heritage- (ICOMOS, 2013), the preventive conservation approach comprises four main steps: analysis, diagnosis, therapy and control.

The analysis searches for substantial information and data; the diagnosis aims identify the individual damage and causes; the therapy defines remedial measures; and, finally, the control step checks the efficiency of the measures adopted (Van Balen, 2013).

#### 1.3 Related work

Some ontologies and data models were created to support cultural heritage data integration and exchange. An ontology consists of a hierarchical finite list of terms and the relationships between these terms, creating a conceptual model for a specific domain. Axioms are used to represent the relationships between the terms and to add a logical layer to the conceptual model (Antoniou, Van Harmelen, 2004). As an example, the following figure shows a fragment of the Monument Damage ontology (MONDIS) (Cacciotti et al., 2013). An ontology that records damages in historical buildings. This fragment shows an object change as a subtype of an event, in turn structural changes, manifestation of damage is repaired by an intervention which prevents another event. Components have materials which may have a manifestation of damages.



Figure 1. MONDIS fragment. Adapted from (Cacciotti et al., 2013).

CIDOC-CRM is the most popular ontology in the cultural heritage domain. It was created by the International Committee for Documentation (CIDOC) of the International Council of Museums (ICOM) (ICOM, 2015). The scope of this ontology is limited to scientific documentation of heterogeneous museum collections and the integration of this documentation in libraries and archives.

<sup>\*</sup> Corresponding author

Heras et. al. (2013) developed a CityGML-ADE model through several interviews and workshops with BCH-managers. The model is based on the building module from the CityGML standard (Kolbe, 2009) which enables a 3D representation of buildings and their components.

The preventive conservation approach is integrated in the model allowing identification of buildings' heritage values, condition and risks. The City-ADE model was implemented using traditional data base management systems.

Zalamea et. al. (2018) present an ontology called BCHontology developed to facilitate interoperability of built cultural heritage information. BCH-ontology merges and expands 3 other ontologies: CIDOC Conceptual Reference Model (CIDOC-CRM) (Doerr, 2009), Geneva City Geographic Markup Language (Geneva-CityGML) (Kolbe, 2009), and Monument Damage ontology (MONDIS) (Cacciotti et al., 2013). The BCH-ontology is based on the CityGML-ADE model developed by Heras et. al.

The BCH-ontology was selected since it is a more complete proposal. An assessment of the response of the user requirements in the BCH domain is presented in this paper. Chapter 2 shows a short description of BCH-ontology and the methodology used for its assessment. Chapter 3 presents the user assessment of the BCH-ontology. Chapter 4 presents the discussion regarding to lessons learned with the ontology validation and the added value of using ontological approaches. Finally, the conclusion is presented in chapter 5.

# 2. METHODOLOGY

#### 2.1 Ontology evaluation

According to Gómez-Pérez et al. (1995) ontology evaluation comprises ontology verification and validation. Ontology verification measures correctness, answering the question: Is the ontology built correctly?, while ontology validation measures quality, looking at how good the ontology models reality, answering whether the correct ontology was built.

The BCH-ontology models the BCH domain under an approach of preventive conservation. To this end, validation is made through use cases where some samples of the preventive conservation approach (PCA) are tested.

# 2.2 BCH-ontology

The BCH-ontology is a tool created to support the exchange and integration of BCH-data under a preventive conservation approach. In this section we describe its background, the study area where it was applied and the its data model.

**2.2.1 BCH-ontology background:** The BCH-ontology was constructed using the city of Cuenca as case of study. It is a World Heritage City designated by UNESCO in 1999 and located in Ecuador, South America. As part of the efforts for improving managing of the built cultural heritage of this location, a Preventive Conservation Approach (PCA) has been fostered.

CityGML-ADE model developed by Heras et. al. has already determined the key elements for preventive conservation: the elements to be monitored and actors to be involved in the process. The BCH-ontology represents this information.



Figure 2. Phases and information of the cycle of Preventive Conservation Approach (Heras et al., 2013).

The BCH-ontology is constructed utilizing 3 already developed ontologies which complement each other to fully cover the BCH-domain shown in Figure 2.

Firstly, the CIDOC-CRM is an ontology created by the International Committee for Documentation (CIDOC) of the International Council of Museums. Its scope is limited to the management of museum collections and libraries. It has been selected as the foundation for the construction of the BCH-ontology because of its high reputation, understandability, and popularity.

Secondly, the CityGML ontology developed by the University of Geneva in 2012 is an ontological version of the CityGML standard developed by the Open Geospatial Consortium (OGC). It allows 3D representation of buildings and their environment. This ontology was chosen since it corresponds with the reality of BCH-data which includes multi-scale and multi-resolution data. BCH is managed at several geographic scales: city level, zones or sectors, sites, buildings, among others. These geographic scales are represented by models with multiple resolutions. CityGML has different levels of detail (LoD), thus multi-scale and multi-resolution are well represented with this standard.

Finally, the Monument Damage Ontology was developed in 2011 by the Czech Republic University in the framework of the MONDIS research project which was supported by the Ministry of Culture of the Czech Republic. MONDIS includes classes for risk assessment. This was the only ontology found for risk assessment in the cultural field. Several applications, such as terminology editors, matrix of knowledge, mondis explorer, among others were developed in test mode to show the ontology utility. With these tools the relationships between the ontology elements are shown.

After its construction, the BCH-ontology was verified using the OntOlogy Pitfall Scanner (Poveda-Villalón et al., 2012), a web tool developed by the Ontology Engineer Group at Polytechnic University of Madrid. The tool is used to detect ontologies anomalies; it supports developers to automatically detect potential errors, improving ontology quality.

The tool was selected since it is easy to use, free of charge, available online and very consistent regarding the type of pitfall it can detect.

OOPS detected the following minor pitfalls: Missing annotations, missing inverse relationships, missing domain or range in properties, and using different naming criteria in the ontology.

In this regard, labels and comments were added for all the classes; inverse properties, domain and ranges were defined for all classes and properties. A name convention was established which is explained in the following section.

**2.2.2 BCH-ontology model:** The BCH-ontology follows a naming convention based on the CIDOC-CRM naming convention in order to homologate names of classes and properties. The CIDOC-CRM identification codes for classes start with the prefix 'E' which stands for 'entity', followed by a sequential number and the name of the class (ICOM, 2015). CIDOC-CRM properties use the prefix 'P'. For the Geneva-CityGML ontology, prefixes 'G' and 'PG' are used to represent classes and properties. MONDIS classes use prefixes 'M' and 'PM'. For new classes, we use the prefix 'HB' since the extension is specific for 'historical buildings', while for properties, we use the prefix 'PHB'. Each word of the class's name is followed by a blank space and starts with upper case, except prepositions. Properties are written with lower case.

The final ontology comprises: 148 classes and 102 properties. Table 1 shows the main classes related to each phase of the preventive conservation approach.

Classes in table 1 will be explained through an example in the following chapter.

Analysis	
M1 CH Object	HB26 Heritage Aspect
M2 Component	HB27 Heritage Dimension
HB1 Building	HB28 Heritage Feature
HB2 Geographic Area	HB29 Conceptual Feature
HB21 Traditional	E26 Physical Feature
Workmanship	HB30 Building Physical
E40 Legal Body	Feature
HB23 Scope	HB31 Decorative Element
HB24 Level of protection	HB32 Organizational Aspect
M4 Manifestation of Damage	HB33 Type of Implantation
HB25 Heritage Value	
Diagnosis	Therapy
<b>Diagnosis</b> HB34 Gravity	Therapy M28 Intervention
Diagnosis HB34 Gravity M3 Risk	Therapy           M28 Intervention
Diagnosis HB34 Gravity M3 Risk M7 Hazard	Therapy M28 Intervention Control
Diagnosis HB34 Gravity M3 Risk M7 Hazard M6 Vulnerability	Therapy         M28 Intervention         Control         HB35 Inspection
Diagnosis HB34 Gravity M3 Risk M7 Hazard M6 Vulnerability E3 Condition State	Therapy         M28 Intervention         Control         HB35 Inspection
Diagnosis HB34 Gravity M3 Risk M7 Hazard M6 Vulnerability E3 Condition State HB45 Performance Status	Therapy         M28 Intervention         Control         HB35 Inspection
Diagnosis HB34 Gravity M3 Risk M7 Hazard M6 Vulnerability E3 Condition State HB45 Performance Status HB48 Therapy	Therapy         M28 Intervention         Control         HB35 Inspection
Diagnosis HB34 Gravity M3 Risk M7 Hazard M6 Vulnerability E3 Condition State HB45 Performance Status HB48 Therapy HB49 Action	Therapy         M28 Intervention         Control         HB35 Inspection
Diagnosis HB34 Gravity M3 Risk M7 Hazard M6 Vulnerability E3 Condition State HB45 Performance Status HB45 Therapy HB49 Action HB52 Resource	Therapy         M28 Intervention         Control         HB35 Inspection
Diagnosis HB34 Gravity M3 Risk M7 Hazard M6 Vulnerability E3 Condition State HB45 Performance Status HB45 Therapy HB49 Action HB52 Resource	Therapy         M28 Intervention         Control         HB35 Inspection

 Table 1. BCH-ontology main classes according the preventive conservation phases.

# 3. VALIDATION OF THE BCH-ONTOLOGY

One historical building from the city of Cuenca was chosen to test whether the BCH-ontology is able to represent the preventive conservation cycle information.



Figure 3. San Luis Seminar - Adapted from claveturismo.com.

The San Luis seminary is a historical building built in the late XIX century in Cuenca. The seminary has a vernacular style materialized by several architectural elements of highly recognized historical value. The seminary will be employed as use case to test the phases of the PCA. The main classes will be explained in detail for the analysis phase, the remaining phases will be explained in a more general manner.

Table 2 shows the terminology used in the following diagrams:

Term	Description
E53 Place	A class represents a category of items that share a number of common features. It is represented by a rectangle.
Instance HB27 Heritage Dimension	A class or a property is instantiated when a value of the real world is assigned to it. For example 'Ecuador' is an instance of the class Place.
Property E18_Physical_Thing P44_has_condition E3_Condition_State	Properties define relationships between two classes. For example, 'historical building has condition stable,' means that a particular historical building from the HB- domain has a state of conservation for example 'Stable.' Properties are represented by a black arrow pointing to the range.
Inheritance M1 CH Object M2 Component	Ontologies show the hierarchical relationship among its classes. This hierarchical representation is also known as inheritance which means the subclass inherits all the properties from the superclass. Inheritance is represented by a white arrow pointing to the superclass.

 Table 2. Representation of building components and heritage values of San Luis seminary.

# 3.1 Analysis

First we have to give a reference name to the seminary which in this case will be: HBSanLuis. The seminary is a building which is represented in Table 1, line 4. For readability reasons the whole classification of components is not shown in Figure 4 but it can be found in Figure A1 in the appendix chapter. The seminary identifier is the cadastral code '0102035001000' (Table 3, line 2) and its address is 'Benigno Malo 9-49 y Bolivar' (Table 3, lines 2, 7-9). The address is represented by the reference name 'AddSanLuis.' Table 3, line 9 indicates that 'AddSanLuis' is an address.



Figure 4. BCH-ontology analysis phase.

The seminary is composed of two facades (Table 3, lines 5, 6). The first one is identified by the reference name 'HB1F1' and the second one by 'HB1F2.' The facade 'HB1F1' is composed of 15 arches, 7 windows and 6 doors (Table 3, line 13-15). An ellipsis (...) is used to indicate the list of components: arches, windows and doors continue.

1	Element: HBSanLuis		
2	P1 is identified by	·0102035001000'	
3	P1 is identified by	AddSanLuis	
4	P2 has type	HB1 Building	
5	P46 is composed of	HB1F1	
6	P46 is composed of	HB1F2	
7	Element: AddSanLuis		
8	P3 has note	'Benigno Malo 9-49 y Bolivar'	
9	P2 has type	E45 Address	
10	Element: HB1F1		
11	P1 is identified by	·0102035001000'	
12	P2 has type	HB8 Facade	
13	P46 is composed of	HB1F1A1	
14			
15	P46 is composed of	HB1F1D6	
16	Element: HB1F1A1		
17	P2 has type	HB11 Arch	

Table 3. Representation of building components and heritage values of San Luis seminary.

Distribution of the components in the facade generates heritage features such as symmetry regarding the central axis (Table 4, line 5), and homogeneous vertical distribution axis (Table 4, line 10) that increase the seminary heritage value (Table 4, line 1). These features are related to the 'Form and design' aspect (Table 4, line 14) and the 'Artistic' dimension (Table 4, line 13).

Table 4, lines 6-9 show the links between the heritage feature 'Central Axis Symmetry' with the heritage value of the first facade, the aspect 'Form and design,' and the dimension 'Artistic.'

BCH-ontology also documents damages. Figure A2 shows the full list of damages classification. For the San Luis seminary a detachment in the facade was documented (Table 4, line 4). Damages are produced by some deterioration agent (Table 4, line 23) such as: Fire, Water, Climate, etc.

The link between the damage and the deterioration agent is shown in Table 4, lines 24-26.

1	Element: HB1F1HV1		
2	P2 has type	HB25 Heritage Value	
3	P64 refers to	HB1F1	
4	P56 bears feature	HB1F1HV1D1	
5	Element: CentralAxisSymmetry		
6	P2 has type	HB28 Heritage Feature	
7	P64 refers to	HB1F1HV1	
8	P64 refers to	HB26Aspect1	
9	P64 refers to	HB27Dimension1	
10	Element: HomogeneousVerticalDistribution		
11	P2 has type	HB28 Heritage Feature	
12	P64 refers to	HB1F1HV1	
13	P64 refers to	HB26Aspect1	
14	P64 refers to	HB27Dimension1	
15	Element: HB26Aspect1		
16	P3 has note Form and design		
17	P2 has type	P2 has type HB26 Heritage Aspect	
18	Element: HB27Dimension1		
19	P3 has note	Artistic	
20	P2 has type	HB27 Heritage Dimension	
21	Element: HB1F1HV1D1		
22	P2 has type	M18 Detachment	
23	PHB4 has Agent	HB1F1HV1D1A1	
24	Element: HB1F1HV1D1A1		
25	P2 has type	M5 Agent	
26	P3 has note	'Water'	

 Table 4. Representation of heritage values, features, aspects and dimensions of San Luis seminary.

# 3.2 Diagnosis

A performance status is computed as a result of the diagnosis phase. Condition, risk and gravity are used to compute the performance status.

For the San Luis seminary, the condition is set as a qualitative value 'Stable' (Table 5, lines 1-3) however it can also be set as a quantitative value (Table 5, lines 10-13) or according to a list of parameters (Figure A3.)

A gravity value (Table 5, lines 10-13) is computed considering damages (Table 5, line 9) that decrease the heritage value of a component. The gravity assignment (Table 5, line 4-6) class links the gravity with the heritage value.

Risk is computed taking into account hazards and vulnerability. With a 'low' vulnerability and a 'medium' hazard, the general risk is evaluated as 'low.' Quantitative values can also be assigned (Table 5, lines 10-13).

Risk, gravity and performance status are linked to the heritage value through the HB41-HB47-HB35 assignment classes. Table 5, lines 14-16 shows the link for risk; the same process is applied for gravity and performance status.



Figure 5. BCH-ontology diagnosis phase.

1	Element: HB1F1HV1C		
2	P2 has type	E3 Condition State	
3	P3 has note	'Stable'	
4	Element: HB1F1HV1GA		
5	P141 assigned HB1F1HV1		
6	P140 assigned attribute to	HB1F1HV1G	
7	Element: HB1F1HV1G		
8	P2 has type HB34 Gravity		
9	PHB5 has damage	HB1F1HV1D1	
10	P43 has dimension	HB1F1HV1Gvalue	
11	Element: HB1F1HV1Gvalue		
12	P2 has type	E54 Dimension	
13	P90 has value 5		
14	Element: HB1F1HV1RA		
15	P141 assigned	HB1F1HV1	
16	P140 assigned attribute to HB1F1HV1R		
17	Element: HB1F1HV1R		
18	P2 has type	M3 Risk	
19	P3 has note	'Low'	
20	M1 refers to hazard	HB1F1HV1H	
21	Element: HB1F1HV1H		
22	P2 has type	M7 Hazard	
23	P3 has note	'Medium'	
24	Element: HB1F1HV1V		
25	P2 has type	M6 Vulnerability	
26	P3 has note	'Low'	
27	M2 is subject to	HB1F1HV1H	

Table 5. Diagnosis phase of San Luis seminary.

# 3.3 Therapy

A therapy (Table 6, line 4-6) is set according the performance status value. The therapy consists of one suggested indirect action 'Special\_plans\_or\_campaigns' (Table 6, lines 9-13) with a budget of 100 euros (Table 6, lines 20-23). Actions have a type (Table 6, lines 11, 14-16) which can be curative or preventive (direct, indirect). The status of the action (Table 6, lines 17-19) can be 'suggested action' or 'executed action.'

After a therapy is suggested, an intervention (Table 6, lines 24-26) may be executed in which case the action changes its status.



Figure 6. BCH-ontology therapy and control phases.

1	Element: HB1F1H	V1PS		
2	P2 has type		HB45	Performance
			Status	
3	HBP15 has therapy		HB1F1F	HV1T
4	Element: HB1F1H	V1T		
5	P2 has type		HB48 Therapy	
6	HBP16 has suggested action		HB1F1HV1A	
7	HBP20 has intervention		HB1F1HV1INT	
8	HBP24 has inspectio	n	HB1F1F	IV1INS
9	Element: HB1F1HV1TA			
10	P3 has note 'Specia		l_plans_or_campaigns'	
11	P2 has type	HB50A	ctionType1	
12	HBP17 has status HB51A		ctionStatus1/	
	HB51A		.ctionStatus2	
13	HBP18 has budget HB1F1		HV1TAB	
14	Element: HB50ActionType1			
15	P2 has type		HB50 Action Type	
16	P3 has note		'Preventive - Indirect'	
17	Element: HB50ActionStatus1			
18	P2 has type		HB51 Action Status	
19	P3 has note		'Suggested action'	
20	Element: HB1F1HV1TAB			
21	P2 has type		E54 Dimension	
22	P90 has value		100	
23	P91 has unit		Euros	
24	Element: HB1F1HV1INT			
25	P2 has type		M28 Intervention	
26	HBP21 has intervention		HB1F1HV1A	
	action			

Table 6. Therapy phase of San Luis seminary.

#### 3.4 Control

In the last phase the class intervention checks whether the conservation objective was reached after the intervention (Table 7, lines 1-4).

1	Element: HB1F1HV1INS		
2	P2 has type	HB53 Inspection	
3	HBP22 requires further inspections	'No'	
4	HBP23 conservation objective reached	'Yes'	

Table 7. Control phase of San Luis seminary.

#### 4. DISCUSSION

#### 4.1 Validation lessons learned

After validating the preventive conservation phases with the BCH-ontology we can conclude that the ontology is able to represent the information of each phase. However, some uncertainties and suggestions related to the documentation of the BCH-ontology arose.

First, there should be some guidelines for the selection of reference names. Some instances refer to features of a specific object like the facade of San Luis seminary 'HB1F1' while others are general instances that can be related to any object like the 'Form and design' aspect whose name in this example is HB26Aspect1. There is no specification of how the names should be established. The naming convention could be improved with some recommendations for the user.

The BCH-ontology classes and properties are well documented; nevertheless, its understandability and quality could be improved by including a user manual with examples of the actual ontology use.

The BCH-ontology provides an organized manner to store information, however it does not provides methodologies for risk assessment, intervention assignments, etc. The logic has to be implemented according to each methodology. Having the option to accommodate quantitative values, qualitative values and a parameters list is desirable, however it does not ensure that complex methodologies can be accommodated. Some examples of how to modify the ontology for other methodologies are also required.

# 4.2 Additional use cases

The main objective of this paper, validating the preventive conservation cycle, was achieved. However, other use cases are suggested to show the advantages of using ontological approaches.

**4.2.1 Heterogeneous data integration:** Another important feature of the ontological approaches is that it supports data integration from heterogeneous data sets. In chapter 3.2, condition, risk, hazard and vulnerabilities can be set as quantitative values, qualitative values or as a result of several parameters. A use case where stakeholders integrate different risk assessment methodologies is suggested, it will be interesting to test how this integration is possible and what are its advantages.

**4.2.2 3D representation of buildings:** 3D feature models are becoming increasingly popular among BCH-managers since they provide interesting possibilities for visualization and analysis (Arízaga Guzmán, 2013). 3D model representation moving towards 3D analyses is the current trend.

In this regard, the inclusion of the CityGML standard into the BCH-ontology is an important asset which has not being tested yet.

Another needed use case should show the added value of having 3D models which go beyond visualization.

# 4.3 Ontologies additional advantages

An ontological model offers additional advantages:

**4.3.1 Multilevel inheritance:** Ontological approaches implement the concept of inheritance in an efficient and practical manner. Superclasses properties can be used by the subclasses in any level without giving further specification. For example, 'P1 is identified by' is a property of the 'E1 CRM Entity' class which is the root class of the BCH-ontology; this property can be used by the remaining 147 classes of the ontology without having to define anything else.

In other data gathering systems such as databases, an inheritance has to be manually implemented. For example, if the BCHontology was implemented using a database and an identifier will be a property of every object, a column named 'identifier' must be added in each of the 148 tables.

**4.3.2 Logical inferences:** The hierarchical structure of ontologies allows some basic inferences. For example: let's image we are integrating information from an external data set where there is not a definition of 'Heritage Building' and the information is just recorded as 'Building' and at some place information such as a component with heritage value is stored.

The ontology can establish a logical rule that states: "If a building or a component of it has a heritage value, then the building is a heritage building."

When the information from the external data set is integrated into the ontology and the information regarding the component with the heritage value is found, the record is automatically classified as 'Heritage Building.' Other records of no-heritage buildings will be stored as well but only as simple buildings. No additional efforts are needed to organize heritage buildings and simple buildings.

If a query is performed, the ontology can make the distinction between these objects and return 'all the buildings' or 'heritage buildings' automatically.

In other approaches, the same queries can be performed but it is the query builder who has to construct the query knowing where the information of building or heritage building is stored. The query builder needs to be well aware of the stored structure. The query builder is the one that knows the logical rule and implements queries according these logical rules while in an ontological approach the logical rule is stored in the same ontology. The query builder just needs to know that there are buildings and heritage buildings, not where or how they are stored.

**4.3.3 No-populated ontologies have information:** Empty data gathering systems cannot answer any query. In traditional systems such as databases, the information is stored after creating a model. The model is just an empty container with no real use.

An empty ontological model can offer plenty of important information. Figure A2, for example, shows that a damage classified as 'Biological colonization' is a damage in the material covering the component rather than in the component itself. It can also be known that if a damage is found in a component it will be: a deformation, displacement, rotation, failure or crack. Figure 3 shows that an action is related to a type, a status, a budget and resources.

All this information can be retrieved without having any data in the ontology.

#### 5. CONCLUSION AND FUTURE WORK

In this research we found the BCH-ontology an appropriate tool for BCH-data exchange. The BCH-ontology proved to be able to implement the whole preventive conservation cycle as shown in Figure 1. Currently, it can be used as a structured glossary of terms.

Since CIDOC-CRM is the foundation of the BCH-ontology, there is guaranteed compatibility with other CRM systems, mainly but not exclusively those explored in section 5.1 (external datasets).

The BCH-ontology is a tool which provides additional values than representing thematic PCA data. It also supports data integration, however these aspects have not been tested in this paper. Future work will consist of the elaboration of more use cases such as those mentioned in chapter 4.

#### REFERENCES

Antoniou, G., Van Harmelen, F., 2004. *A Semantic Web Primer*. Massachusetts Institute of Technology.

Arízaga Guzmán, D., 2013. El Decreto de Emergencia del Patrimonio Cultural del Ecuador, una apuesta de construcción de políticas públicas para la conservación del Patrimonio Cultural en el país. *III ENCUENTRO PRECOM3OS, Desafíos de La Conservación Preventiva. Seminario Para Estudiantes Doctorales, Expertos y Gestores de Sitios Patrimoniales*, 111–122.

Cacciotti, R., Valach, J., Kunes, P., Cernansky, M., Blasko, M., Kremen, P., 2013. MONUMENT DAMAGE INFORMATION SYSTEM (MONDIS): AN ONTOLOGICAL APPROACH TO CULTURAL HERITAGE DOCUMENTATION. *ISPRS Annals* of the Photogrammetry, Remote Sensing and Spatial Information Science, 55–60.

Doerr, M., 2009. Ontologies for Cultural Heritage. In S. Staab, R. Studer (Eds.), *Handbooks on Ontologies*. (2nd ed.). Springer.

Forster, A., Kayan, B., 2009. *Maintenance for historic buildings:* A current perspective. 210–229.

Gómez-Pérez, A., Juristos, N., Pazos, J., 1995. Evaluation and assessment of the knowledge sharing technology. In *Towards Very Large Knowledge Bases* (1st ed., pp. 289–296). IOS Press Amsterdam.

Hart, G., 2008, September. *Linking to the past, geographically speaking: The Linked Data Web and Historical GIS.* Workshop: 'The Cultural Heritage of Historic European Cities and Public Participatory GIS.'

Heras, V., Steenberghen, T., Zalamea, O., 2013. A GIS based tool for a Preventive Conservation Management Approach. In *Reflections on Preventive Conservation, Maintenance and Monitoring of Monuments and Sites - PRECOM3OS UNESCO Chair* (pp. 86–93). ACCO.

ICOM., 2015. Definition of the CIDOC Conceptual Reference Model. ICOM. http://www.cidoc-crm.org/Version/version-5.0.4 ICOMOS. (1931). The Athens Charter for the Restoration of Historic Monuments. http://www.icomos.org/en/charters-andtexts/179-articles-en-francais/ressources/charters-andstandards/167-the-athens-charter-for-the-restoration-of-historicmonuments ICOMOS, 1964. International Charter for the Conservation and Restoration of Monuments and sites. https://www.icomos.org/charters/venice\_e.pdf

ICOMOS, 2003. "The Burra Charter". The Burra Charter was first adopted in 1979 at the historic South Australian mining town of Burra. Minor revisions were made in 1981, 1988, 1999, 2013.

ICOMOS, 2013. Charter - Principles for the Analysis, Conservation and Structural Restoration of Architectural Heritage, Victoria Falls (Zimbabwe), 2003. http://www.icomos.org/charters/structures\_e.pdf

Kolbe, T. H., 2009. Representing and Exchanging 3D City Models with CityGML. In *3D Geo-Information Sciences* (Jiyeong Lee, Sisi Zlatanova, pp. 15–31). Springer Berlin Heidelberg. http://link.springer.com/chapter/10.1007%2F978-3-540-87395-2\_2

Poveda-Villalón, M., Suárez-Figueroa, M. C., Gomez-Perez, A., 2012. Validating ontologies with OOPS! 267–281. https://doi.org/10.1007/978-3-642-33876-2\_24

Van Balen, K., 2013. Preventive Conservation in an International context and its challenges discussed at the PRECOMOS seminar. In *Cardoso F., Rodas Vasquez C. (Eds.), III ENCUENTRO PRECOM3OS, Desafíos de la Conservación Preventiva. Seminario para estudiantes doctorales, expertos y gestores de sitios patrimoniales* (pp. 5–18).

Zalamea, O., Van Orshoven, J., Steenberghen, T., 2018. *Merging* and expanding existing ontologies to cover the Built Cultural *Heritage domain*.

# APPENDIX



Figure A1. BCH-ontology representation of components type.



Figure A2. BCH-ontology representation of damages.



Figure A3. BCH-ontology condition state and performance status representation.